

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SYNTECH PAVISTRONG COMP. A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Preparation for building and construction: Two-component epoxy coating resistant. Component A

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

Street : Via G. Gentile 16/A

Postal code/city : 46044 Goito (MN)

Telephone : +39 0376 604185 / 604365

Telefax : +39 0376 604398

Information contact : info@azichem.com

1.4 Emergency telephone number

Centro Antiveleni di Milano +39 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)
Centro Antiveleni di Pavia +39 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Bergamo +39 800 883300 (CAV Ospedali Riuniti - Bergamo)
Centro Antiveleni di Firenze +39 055 7947819 (CAV Ospedale Careggi - Firenze)
Centro Antiveleni di Roma +39 06 3054343 (CAV Policlinico Gemelli - Roma)
Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)
Centro Antiveleni di Napoli +39 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

RESINS, BISPHENOL F-EPICHLOROHYDRIN ; CAS No. : 9003-36-5

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <=

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

700) ; CAS No. : 25068-38-6

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.

Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

RESINS, BISPHENOL F-EPICHLOROHYDRIN ; EC No. : 500-006-8; CAS No. : 9003-36-5

Weight fraction : $\geq 30 - < 50$ %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

TITANIUM DIOXIDE ; EC No. : 236-675-5; CAS No. : 13463-67-7

Weight fraction : $\geq 9 - < 30$ %
Classification 1272/2008 [CLP] : None

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) ; CAS No. : 25068-38-6

Weight fraction : $\geq 9 - < 25$ %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

2-METHOXY-1-METHYLETHYL ACETATE ; REACH registration No. : 01-2119475791-29 ; EC No. : 203-603-9; CAS No. : 108-65-6

Weight fraction : $\geq 5 - < 9$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226
Substance with a common (EC) occupational exposure limit value.

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC ; EC No. : 265-199-0; CAS No. : 64742-95-6

Weight fraction : $\geq 2,5 - < 5$ %
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

1,2,4-TRIMETHYLBENZENE ; EC No. : 202-436-9; CAS No. : 95-63-6

Weight fraction : $\geq 1 - < 2,5$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335 Aquatic Chronic 2 ; H411

XYLENE ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction : $\geq 0 - < 0,5$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

ETHYLBENZENE ; EC No. : 202-849-4; CAS No. : 100-41-4
Weight fraction : $\geq 0 - < 0,5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H332

CUMENE ; EC No. : 202-704-5; CAS No. : 98-82-8
Weight fraction : $\geq 0 - < 0,5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 Aquatic Chronic 2 ; H411

MESITYLENE ; EC No. : 203-604-4; CAS No. : 108-67-8
Weight fraction : $\geq 0 - < 0,5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H335 Aquatic Chronic 2 ; H411

Additional information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

4.2 Most important symptoms and effects, both acute and delayed

Acute effects : Contact with eyes causes irritation , symptoms may include : redness, swelling , pain, and tearing. For skin contact may cause irritation, erythema , edema, dryness and chapped skin. Inhalation of vapors may cause mild irritation of the upper respiratory tract. Ingestion may cause health problems , including stomach pain and sting, nausea and vomiting. Upon contact with the skin it causes a sensitization (contact dermatitis) . Dermatitis derives in response to an inflammation of the skin , that begins in the skin areas that come into repeated contact with the sensitizing agent . The skin lesions may include erythema, edema, papules, vesicles , pustules, scales , ulcerations and exudative phenomena , which vary depending on the stage of the disease and the affected areas. In the acute phase prevail erythema , edema and exudation . In the chronic stages prevail scales , dryness, ulcerations and skin thickening .

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO2) Water mist

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide.

5.3 Advice for firefighters

Remove persons to safety.

Special protective equipment for firefighters

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

For non-emergency personnel

Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

Hints on joint storage

Storage class : 3

Storage class (TRGS 510) : 3

Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

8.1 Control parameters

Occupational exposure limit values

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 270 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 06.11.2015

Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 550 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 275 mg/m³
Remark : H
Version : 08.06.2000

1,2,4-TRIMETHYLBENZENE ; CAS No. : 95-63-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 20 ppm / 100 mg/m³
Peak limitation : 2(II)
Remark : Y
Version : 06.11.2015

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 100 mg/m³
Version : 08.06.2000

CUMENE ; CAS No. : 98-82-8

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 50 mg/m³
Peak limitation : 4(II)
Remark : H,Y
Version : 06.11.2015

Limit value type (country of origin) : STEL (EC)
Limit value : 50 ppm / 250 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 100 mg/m³
Remark : H
Version : 08.06.2000

MESITYLENE ; CAS No. : 108-67-8

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 20 ppm / 100 mg/m³
Peak limitation : 2(II)
Remark : Y
Version : 06.11.2015

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 100 mg/m³
Version : 08.06.2000

Biological limit values

CUMENE ; CAS No. : 98-82-8

Limit value type (country of origin) : TRGS 903 (D)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Parameter : 2-Phenyl-2-propanol / Urine (U) / End of exposure or end of shift
Limit value : 10 mg/g Kr
Version : 01.05.2015

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL Consumer (systemic) (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Exposure route : Oral
Exposure frequency : Long-term (repeated)
Limit value : 700 mg/kg
Limit value type : DNEL worker (systemic) (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 10 mg/m³

PNEC

Limit value type : PNEC aquatic, freshwater (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 0,12 mg/l
Limit value type : PNEC aquatic, intermittent release (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 0,61 mg/l
Limit value type : PNEC aquatic, marine water (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 1 mg/l
Limit value type : PNEC sediment, freshwater (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 1000 mg/kg
Limit value type : PNEC sediment, marine water (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 100 mg/kg
Limit value type : PNEC Soil (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 100 mg/kg
Limit value type : PNEC sewage treatment plant (STP) (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Limit value : 100 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment



When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection

Safety glasses with side shields (EN 166).

Skin protection

Hand protection

Wear rubber gloves approved under standard EN374.

Respiratory protection

In case of exceeding the threshold value (if available) of one or more of the substances present in the product, for daily exposure in the workplace or to a fraction established by the service of prevention and protection service, wear a mask with filter type B or universal, the class (1, 2 or 3) must be chosen according to the limit concentration of use (ref. standard EN 141).

SECTION 9: Physical and chemical properties

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

9.1 Information on basic physical and chemical properties

Safety relevant basis data

Aspect		liquid
Colour		White or colored
Odour		pungent
Melting point/melting range :	(1013 hPa)	No data available
Vapour density	(air = 1)	Data not available
Initial boiling point and boiling range :	(1013 hPa)	No data available
Decomposition temperature :		No data available
Self flammability		No data available
Flash point :	>	44 °C
Flammability (solid, gas)		Data not available
Lower explosion limit :		No data available
Upper explosion limit :		No data available
Explosive properties		Data not available
Vapour pressure	(20 °C)	No data available
Density :	(20 °C)	1,25 - 1,35 g/cm ³
Density :	(23 °C)	No data available
Water solubility :	(20 °C)	insoluble
pH :		No data available
Log Pow	(20 °C)	not applicable
Viscosity :	(20 °C)	No data available
Viscosity :	(23 °C)	No data available
Odour threshold		Data not available
Evaporation rate		Data not available
Maximum VOC content (EC) :		1999/13/EC
Oxidizing properties		Data not available

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

See section 7. No additional measures necessary.

10.3 Possibility of hazardous reactions

Certain vapours form explosive mixtures with air.

10.4 Conditions to avoid

Keep away from fire, sparks and ignition sources

10.5 Incompatible materials

Acids and strong oxidants. Alkali metals.

10.6 Hazardous decomposition products

Carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50 (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Exposure route : Oral
Species : Rat
Effective dose : > 5000 mg/kg
Parameter : LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route : Oral
Species : Rat
Effective dose : 6190 mg/kg
Parameter : LD50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route : Oral
Species : Rat
Effective dose : 8700 mg/kg
Parameter : LD50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Exposure route : Oral
Species : Rat
Effective dose : 3500 mg/kg
Parameter : LD50 (CUMENE ; CAS No. : 98-82-8)
Exposure route : Oral
Species : Rat
Effective dose : 1400 mg/kg

Acute dermal toxicity

Parameter : LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 5000 mg/l
Parameter : LD50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route : Dermal
Species : Rabbit
Effective dose : 2000 mg/kg
Parameter : LD50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Exposure route : Dermal
Species : Rabbit
Effective dose : 5000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Exposure route : Inhalation
Species : Rat
Effective dose : > 6,82 mg/l
Exposure time : 4 h
Parameter : LC0 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route : Inhalation
Species : Mouse
Effective dose : > 10 mg/m³
Exposure time : 3 h
Parameter : LC50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route : Inhalation
Species : Rat
Effective dose : 6350 mg/l
Parameter : LC50 (CUMENE ; CAS No. : 98-82-8)
Exposure route : Inhalation
Species : Rat
Effective dose : 8000 ppm

Irritant and corrosive effects

Primary irritation to the skin

Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

Irritation to eyes

Causes eye irritation.

Irritation to respiratory tract

Not an irritant.

Sensitisation

In case of skin contact

May cause sensitization by skin contact.

Repeated dose toxicity (subacute, subchronic, chronic)

There were no chronic effects or effects at low concentrations.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR according to CLP.

SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 134 mg/l
Exposure time : 96 h

Parameter : LC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species : Oryzias latipes (Ricefish)
Effective dose : 63,5 mg/l
Exposure time : 14 days

Acute (short-term) daphnia toxicity

Parameter : EC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Species : Daphnia magna (Big water flea)
Effective dose : 2,8 mg/l
Exposure time : 48 h

Bacteria toxicity

Parameter : EC50 (TITANIUM DIOXIDE ; CAS No. : 13463-67-7)
Species : Activated sludge
Effective dose : > 1000 mg/l
Exposure time : 3 h

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINTS · FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC · 2-METHOXY-1-METHYLETHYL ACETATE)

Sea transport (IMDG)

PAINTS · FLAMMABLE LIQUID, N.O.S. (RESINS, BISPHENOL F-EPICHLOROHYDRIN · REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) · SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC · 2-METHOXY-1-METHYLETHYL ACETATE · 1,2,4-TRIMETHYLBENZENE)

Air transport (ICAO-TI / IATA-DGR)

PAINTS · FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC · 2-METHOXY-1-METHYLETHYL ACETATE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : 640E · LQ 7 · LQ 5 I · E 1
Hazard label(s) : 3 / N

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes

Sea transport (IMDG) : Yes (P)

Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) 1907/2006/CE (REACH). Regulation (EC) No 1272/2008 (CLP). Regulation (EU) 2015/830 requirements for the compilation of safety data sheets. Commission Regulation (EC) No 790/2009/CE (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 286/2011 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 618/2012 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 487/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 758/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 944/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 605/2014 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 1297/2015 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008).

Other regulations (EU)

Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List

None

National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 03. Hazardous ingredients · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR)

16.2 Abbreviations and acronyms

LEGENDA:

ADR:	Accord européen relative au transport international des marchandises dangereuses par route (accordo europeo relativo al trasporto internazionale delle merci pericolose su strada)
ASTM:	ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)
EINECS:	European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze chimiche in Commercio)
EC(0/50/100):	Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50/100% degli Individui)
LC(0/50/100):	Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50/100% degli Individui)
IC50:	Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)
NOEL:	No Observed Effect Level (Dose massima senza effetti)
NOEC:	No Observed Effect Concentration (Concentrazione massima senza effetti)
LOEC:	Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un effetto)
DNEL:	Derived No Effect Level (Dose derivata di non effetto)
DMEL:	Derived Minimum Effect Level (Dose derivata di minimo effetto)
CLP:	Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)
CSR:	Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100):	Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)

IATA:	International Air Transport Association (Associazione Internazionale del Trasporto Aereo)
ICAO:	International Civil Aviation Organization (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG:	International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)
PBT:	Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)
RID:	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)
STEL:	Short term exposure limit (limite di esposizione a breve termine)
TLV:	Threshold limit value (soglia di valore limite)
TWA:	Time Weighted Average (media ponderata nel tempo)
UE:	Unione Europea
vPvB:	Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)
N.D.:	Non disponibile.
N.A.:	Non applicabile
VwVwS.:	Text of Administrative Regulation on the Classification of Substances hazardous to waters into Water Hazard Classes (Verwaltungsvorschrift wassergefährdende Stoffe – VwVWS)
PNEC:	Predicted No Effect Concentration
PNOS:	Particulates not Otherwise Specified
BOD:	Biochemical Oxygen Demand
COD:	Chemical Oxygen Demand
BCF:	BioConcentration Factor
TRGS :	Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The Federal Institute for Occupational Safety and Health, Germany
LCLo:	Lethal Concentration Low (La minima concentrazione letale)
ThOD:	Theoretical Oxygen Demand

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH PAVISTRONG COMP. A
Revision date : 14.05.2017
Print date : 04.06.2017

Version (Revision) : 2.0.0 (1.0.0)
